



△x				TOLERANCE	<table border="1"> <tr><td>L</td><td>4</td><td>±0.1</td></tr> <tr><td>4 < L</td><td>16</td><td>±0.2</td></tr> <tr><td>16 < L</td><td>63</td><td>±0.3</td></tr> <tr><td>63 < L</td><td>250</td><td>±0.4</td></tr> <tr><td>250 < L</td><td></td><td>±0.6</td></tr> </table>	L	4	±0.1	4 < L	16	±0.2	16 < L	63	±0.3	63 < L	250	±0.4	250 < L		±0.6	SCALE	CHECKED by	APPROVED by	MATERIAL	DESCRIPTION
					L	4	±0.1																		
					4 < L	16	±0.2																		
16 < L	63	±0.3																							
63 < L	250	±0.4																							
250 < L		±0.6																							
	ISSUED 2014.10.08	DRAWN by 野中	PLANNED by 長瀬	JFE-CC-JN t=1.2 RoHS対応のこと	ライブユニット																				
				UNIT mm	ANGLE 3rd	REVISED		FINISH (COLOR) 塗装一級:N1三分ツヤ,マスク有 シボ:日本イッチングHN2002	LU2外觀図																
△x	△x	△x	△x						MODEL No.	PART No.	SHEET														
STAMP	DATE		REVISION	SIGN.					23 - 6729	25 - 2653 - 02	/														