



突起部は寸法に含みません

| TOLERANCE | | | UNIT | mm | ANGLE | 3rd | △ x | | | | | | | | | | | | | | | | | | |
|--|------------|------------|-------------|-------|----------|------------------|-----|---------------------|--------|-------|------|--------|-----|------|---------|--|------|--------|--|-------|--|-----|--|--|--|
| <table><tr><td>L</td><td>4</td><td>±0.1</td></tr><tr><td>4 < L</td><td>16</td><td>±0.2</td></tr><tr><td>16 < L</td><td>63</td><td>±0.3</td></tr><tr><td>63 < L</td><td>250</td><td>±0.4</td></tr><tr><td>250 < L</td><td></td><td>±0.6</td></tr></table> | | | L | 4 | ±0.1 | 4 < L | 16 | ±0.2 | 16 < L | 63 | ±0.3 | 63 < L | 250 | ±0.4 | 250 < L | | ±0.6 | ISSUED | | SCALE | | △ x | | | |
| L | 4 | ±0.1 | | | | | | | | | | | | | | | | | | | | | | | |
| 4 < L | 16 | ±0.2 | | | | | | | | | | | | | | | | | | | | | | | |
| 16 < L | 63 | ±0.3 | | | | | | | | | | | | | | | | | | | | | | | |
| 63 < L | 250 | ±0.4 | | | | | | | | | | | | | | | | | | | | | | | |
| 250 < L | | ±0.6 | | | | | | | | | | | | | | | | | | | | | | | |
| | | | 2003.06.09 | | △ x | | | | | | | | | | | | | | | | | | | | |
| | | | REVISED | | △ x | | | | | | | | | | | | | | | | | | | | |
| | | | 2013.04.26 | | △ x | | | | | | | | | | | | | | | | | | | | |
| DRAWN by | PLANNED by | CHECKED by | APPROVED by | △ x | | | | | | | | | | | | | | | | | | | | | |
| 野中 | 諸岡 | | | △ x 1 | 08.03.10 | RoHS対応による改訂 | | | 松村 | | | | | | | | | | | | | | | | |
| | | | | STAMP | DATE | REVISION | | | SIGN. | | | | | | | | | | | | | | | | |
| MATERIAL | | | | | | DESCRIPTION | | | | | | | | | | | | | | | | | | | |
| JFE-CC-JN(ケムリ-鋼板) t1.2 | | | | | | E シリーズ (RoHS対応品) | | | | | | | | | | | | | | | | | | | |
| FINISH (COLOR) | | | | | | E 8 1 A 外観図 | | | | | | | | | | | | | | | | | | | |
| 塗装:2.5Y5/1半ツヤメタリック中目後、シルク印刷 | | | | | | MODEL No. | | PART No. | | SHEET | | | | | | | | | | | | | | | |
| | | | | | | 2 3 - 4 9 1 5 | | 2 5 - 1 9 5 8 - 0 1 | | ／ | | | | | | | | | | | | | | | |